



ABC SYSTEMS AG

APPLIED BRAINWARE & COMPUTER SYSTEMS

Supermicro A+ Family

Outstanding Performance
Drives Business Agility



AMD
EPYC

+41 43 433 6 433

www.abcsystems.ch



Supermicro's latest portfolio of A+ server and storage systems supporting the 2nd Generation AMD EPYC™ processors, offers new levels of optimized performance per watt per dollar, and deliver higher core density, more memory bandwidth, and unparalleled I/O performance and capacity.


Supporting up to 64 AMD "Zen" 2 cores and 128 threads per socket, Supermicro A+ solutions are coupled with high-throughput, low-latency, hot-swappable U.2 NVMe SSDs, up to 4TB of DDR4-3200MHz memory (8 memory channels per socket), and up to 128 PCI-E lanes on a dual- or single-socket system.

Supermicro's new generation A+ solutions supporting AMD EPYC™ family of processors enable a new range of powerful and energy-efficient server options to radically lower data center TCO through an optimized balance of compute, memory, I/O, and storage resources.

For more information, please visit www.supermicro.com/epyc



COVERING KEY WORKLOADS WITH A+ FAMILY



New H12 Generation WIO SuperServer®

COST AND ENERGY EFFICIENCY FOR DATA CENTER ENVIRONMENTS



1U WIO 3.5" Drive Bays



1U WIO 2.5" Drive Bays

Single AMD EPYC™ 7002 Series processors, up to 225W TDP

8 DDR4-3200MHz DIMM slots

3 PCI-E 4.0 x16 slots (2 FHFL and 1 LP slots)

3.5" SATA3 storage (up to 4 optional U.2 NVMe)

2.5" SATA3 storage (up to 2 optional U.2 NVMe)

Dual 10G Ethernet onboard networking

Learn more on page 6

ABC SYSTEMS AG
APPLIED BRAINWARE & COMPUTER SYSTEMS

+41 43 433 6 433

www.abcsystems.ch

New H12 Generation Twin Family

INNOVATIVE MULTI-NODE ARCHITECTURES WITH REDUCED TCO AND TCE



2U TwinPro 4-Node 3.5" Drive Bays



2U BigTwin 4-Node 2.5" Drive Bays

Single AMD EPYC™ 7002 Series per node, up to 225W TDP

8 DDR4-3200MHz DIMM slots per node

2 PCI-E 4.0 x16 slots (2 LP slots) per node

3x 3.5" SATA3 storage per node

Onboard flexible SIOM networking up to 100G

Learn more on page 8

Dual AMD EPYC™ 7002 Series per node, up to 225W TDP*

16 DDR4-3200MHz DIMM slots per node

2 PCI-E 4.0 x16 slots (2 LP slots) per node

6x 2.5" SATA3 storage per node

Onboard flexible SIOM networking up to 100G


Learn more on page 10 * Conditional, restrictions may apply

H12 Generation WIO SuperServer®

COST AND ENERGY EFFICIENCY FOR DATA CENTER ENVIRONMENTS

Single-socket cost-effective systems in 1U
10x 2.5" or 4x 3.5" hot-swappable drive bays
Onboard dual 10 Gigabit Ethernet networking

Supermicro WIO SuperServer® systems offer a wide range of I/O options to deliver truly optimized systems for specific requirements. Users can optimize the storage and networking alternatives to accelerate performance, increase efficiency and find the perfect fit for their applications. In addition to enabling customizable configurations and optimization for multiple application requirements, Supermicro WIO SuperServers also provide attractive cost advantages and investment protection.



1U 4x 3.5" Hot-swap Drive Bays



1U 10x 2.5" Hot-swap Drive Bays




Rackmount

Up to 10x 2.5" drive bays in 1U;
Up to 4x 3.5" drive bays in 1U



1-Socket

Up to AMD EPYC™ 7002 series processors;
up to 225W



8 DIMM Slots

Up to 2TB ECC memory with 256GB
DIMMs, up to DDR4-3200MHz



NVMe/SATA3

Hybrid backplane supporting NVMe and
SATA3 drives; 2 PCI-E 4.0 x4 M.2 slots



Onboard Networking

Dual 10GbE RJ45 LAN ports with dedicated
IPMI LAN port;
2 PCI-E 4.0 x16 FHFL slots and 1 PCI-E 4.0
x16 LP slot in 1U




Platinum Level

Up to redundant 500W high-efficiency
digital power supplies

H12 Generation TwinPro™


INNOVATIVE MULTI-NODE ARCHITECTURE WITH REDUCED TCO AND TCE

TwinPro systems are designed for simplified deployment and maintenance, and assembled with the highest quality to ensure continuous operation even at maximum capacity. Customers in high-end enterprise, data center, HPC and Cloud Computing environments receive the greatest competitive advantage from data center resources with the Supermicro TwinPro.



Node View

Single EPYC® processors supported
8 DIMMs for up to 2 TB of memory



System Rear View



2U 4-Node 3.5" Front View



FORM-FACTOR

Four Nodes

Four sets of 3x 3.5" drives



STORAGE

SATA3

4 M.2 NVMe/SATA slots per node



CPU

1-Socket

Up to AMD EPYC™ 7002 series processors;
up to 225W



I/O

Flexible Networking

Super I/O Module (SIOM) networking*
with dedicated IPMI LAN port per node;
Up to 2 PCI-E 4.0 x16 LP slots



MEMORY

8 DIMM Slots

Up to 2TB ECC memory with 256GB
DIMMs per node, up to DDR4-3200MHz



POWER SUPPLY

Platinum Level


Up to redundant 2000W high-efficiency
digital power supplies

H12 Generation BigTwin™


NO-COMPROMISE 2U 4-NODE TWIN ARCHITECTURE

2U systems supporting four nodes with 16 DIMM slots
Flexible storage options including all NVMe and hybrid NVMe/SAS3/SATA3
SIOM networking options including 10GbE, 25GbE, 100GbE and IB

The new H12 generation 2U BigTwin design supports the latest AMD EPYC™ 7002 series processors with up to 16 DIMMs of DDR4-3200MHz memory, two PCI-E 4.0 x16 LP expansion slots, flexible onboard networking via SIOM, and up to six 2.5" drive bays per node, with additional options for SAS3 storage.



Node View
Dual EPYC™ processors supported
16 DIMMs for up to 4 TB of memory



System Rear View



All-Flash NVMe



Hybrid NVMe/SAS3/SATA3



SATA3 Model



Four Nodes
Four sets of 6x 2.5" drives



2-Socket
Up to AMD EPYC™ 7002 series processors;
up to 225W**



Up to 16 DIMM Slots
Up to 4TB ECC memory with 256GB
DIMMs per node, up to DDR4-3200MHz



NVMe/SAS3/SATA3
All NVMe or SATA3 or hybrid NVMe/SAS3;
1 NVMe/SATA3 M.2 slot per node



Flexible Networking
Super I/O Module (SIOM) networking*
with dedicated IPMI LAN port per node;
Additional 2 PCI-E 4.0 x16 LP slots



Up to Titanium Level
Up to redundant 2600W high-efficiency
digital power supplies

H11 Ultra

INDUSTRY LEADING IOPS, ENERGY EFFICIENCY
AND FLEXIBILITY



Dual AMD EPYC™ 7002 Series, up to 225W TDP

32 DDR4-3200MHz DIMM slots

Up to 7 PCI-E 3.0 slots

2.5" or 3.5" SATA3, SAS3, Hybrid and All-NVMe storage

Flexible onboard networking up to 2x 25G Ethernet

Learn more on page 14

H11 BigTwin™

NO-COMPROMISE 2U 4-NODE TWIN
ARCHITECTURE



Dual AMD EPYC™ 7002 Series per node, up to 225W TDP

16 DDR4-3200MHz DIMM slots per node

2 PCI-E 3.0 x16 slots (2 LP slots)

2.5" All-NVMe/Hybrid SAS3 storage

Onboard flexible SIOM networking up to 100G Ethernet

Learn more on page 16

H11 WIO

EFFICIENCY AND STORAGE OPTIMIZED
ARCHITECTURE



Single AMD EPYC™ 7002 Series, up to 225W TDP

16 DDR4-3200MHz DIMM slots

Up to 5 PCI-E 3.0 slots (3 FHFL and 2 LP slots)

U.2 NVMe or 2.5" SATA3 storage

Onboard networking dual 10G Ethernet

Learn more on page 18

+ 41 43 433 6 433

H11 Mainstream

EFFICIENT, COST-EFFECTIVE DESIGNS
FOR THE MAINSTREAM



Single or dual AMD EPYC™ 7002 Series, up to 225W TDP

Up to 16 DDR4-3200MHz DIMM slots

Up to 6 PCI-E 3.0 slots

3.5" SATA3 and optional SAS3 storage

Onboard networking up to dual 10G Ethernet


Learn more on page 20

www.abcsystems.ch

H11 Generation Ultra

INDUSTRY LEADING IOPS, ENERGY EFFICIENCY AND FLEXIBILITY

Supermicro Ultra SuperServers are designed to deliver the highest performance, flexibility, scalability and serviceability to demanding IT environments, and to power mission-critical Enterprise workloads



1U/2U systems supporting dual processors with 32 DIMM slots
Versatile storage options with U.2 NVMe, SAS3 and SATA3
Flexible networking for up to 25G Ethernet and PCI-E expansion options



1U Ultra 4x 3.5" Drive Bays



FORM-FACTOR

Rackmount

Up to 10x 2.5" or 4x 3.5" drive bays in 1U;
Up to 24x 2.5" or 12x 3.5" drive bays in 1U



STORAGE

NVMe/SAS3/SATA3

1 PCI-E/SATA M.2 support on some models



2U Ultra 12x 3.5" Drive Bays



CPU

2-Socket

Up to AMD EPYC™ 7002 series processors;
up to 225W




I/O

Flexible Networking

Rich PCI-E expansion options including
GPU support; Flexible networking via
Ultra Riser adapters* with dedicated IPMI
LAN port



1U Ultra 24x 2.5" NVMe Drive Bays



MEMORY

32 DIMM Slots

Up to 8TB ECC memory with 256GB
DIMMs, up to DDR4-3200MHz



POWER SUPPLY

Up to Titanium Level


Up to redundant 1600W high-efficiency
digital power supplies

H11 Generation BigTwin™


NO-COMPROMISE 2U 4-NODE TWIN ARCHITECTURE

2U systems supporting four independent nodes with 16 DIMM slots
Flexible storage options including all NVMe and hybrid NVMe/SAS3/SATA3
SIOM networking options including 10GbE, 25GbE, 100GbE and IB

BigTwin is the 5th generation in the Supermicro Twin Family with a multitude of innovations and engineering breakthroughs. Historically multi-node systems traded off features and capacity for higher density. They were deployed for workloads that did not require the highest performance or the highest memory density on a single node.



Node View
Dual EPYC™ processors supported
16 DIMMs for up to 4 TB of memory



Rear System View



All-Flash NVMe



Hybrid NVMe/SAS3/SATA3




SATA3 Model



Four Nodes
Four sets of 6x 2.5" drives



2-Socket
Up to AMD EPYC™ 7002 series processors
per node; up to 225W**



Up to 16 DIMM Slots
Up to 4TB ECC memory with 256GB
DIMMs per node, up to DDR4-3200MHz



NVMe/SAS3/SATA3
All NVMe or SATA3 or hybrid NVMe/SAS3;
1 NVMe/SATA3 M.2 slot per node



Flexible Networking
Super I/O Module (SIOM) networking*
with dedicated IPMI LAN port per node;
Additional 2 PCI-E 3.0 x16 LP slots




Up to Titanium Level
Up to redundant 2600W high-efficiency
digital power supplies

H11 Generation WIO SuperServer®

EFFICIENCY AND STORAGE OPTIMIZED ARCHITECTURE

Single-socket cost-effective systems in 1U/2U
Up to 10 U.2 NVMe in 1U or 24 U.2 NVMe storage devices in 2U
Onboard dual 10 Gigabit Ethernet networking

Supermicro WIO SuperServer® systems offer a wide range of I/O options to deliver truly optimized systems for specific requirements. Users can optimize the storage and networking alternatives to accelerate performance, increase efficiency and find the perfect fit for their applications. In addition to enabling customizable configurations and optimization for multiple application requirements.



1U 10x 2.5" Hot-swap Drive Bays



Rackmount

Up to 10x 2.5" drive bays in 1U;
Up to 24x 2.5" drive bays in 2U



All-NVMe/SATA3

Hybrid backplane supporting NVMe and SATA3 drives; 2 PCI-E 3.0 x4 M.2 slots



1U 24x 2.5" Hot-swap Drive Bays



1-Socket

Up to AMD EPYC™ 7002 series processors;
up to 225W



Onboard Networking

Dual 10GbE RJ45 LAN ports with dedicated IPMI LAN port;
Up to 3 PCI-E 3.0 slots in 1U and 5 slots in 2U



2U 16x 2.5" Hot-swap Drive Bays



16 DIMM Slots

Up to 4TB ECC memory with 256GB DIMMs, up to DDR4-3200MHz




Up to Titanium Level

Up to redundant 1200W high-efficiency digital power supplies

H11 Generation Mainstream SuperServer®

EFFICIENT, COST-EFFECTIVE DESIGNS FOR THE MAINSTREAM APPLICATIONS

1U, 2U and tower systems supporting single or dual processors
1-socket and 2-socket models for optimal efficiency and performance
Hot-swappable 3.5" SATA3 with SAS3 options



Server Board

Dual EPYC® processors supported
16 DIMMs for up to 2 TB of memory
(for tower system shown on the right only)



Tower 2-Socket 3.5" Hot-swap Drive Bays



1U 4x 3.5" Hot-swap Drive Bays



2U 8x 3.5" Hot-swap Drive Bays



FORM-FACTOR



CPU



MEMORY

Rackmount and Tower

4x 3.5" drive bays in 1U; 8x 3.5" drive bays in 2U; 8x 3.5" and 2x 5.25" drive bays in 4U tower

1 or 2-Socket

Up to AMD EPYC™ 7002 series processors;
up to 225W

Up to 16 DIMM Slots

Up to 4TB ECC memory with 256GB DIMMs, up to DDR4-3200MHz



STORAGE



I/O



POWER SUPPLY

SAS3/SATA3

Up to 8x 3.5" SAS3 drives via Broadcom 3008 in 2U; PCI-E M.2 support available

Onboard Networking


Up to dual 10GbE with dedicated IPMI LAN port; Up to 6 PCI-E 3.0 slots

Up to Platinum Level

Up to redundant 1280W high-efficiency digital power supplies

H12 Generation WIO Serverboard

PCI-E 4.0 READY OPTIMIZED FOR THE WIO PLATFORM



NEW! H12SSW


Single-socket WIO Form-Factor

- Up to 2nd Gen AMD EPYC processors, up to 225W TDP
- 8 DIMM slots, up to DDR4-3200MHz
- 3 PCI-E 4.0 x16 and 2 M.2 slots
- Up to 16 SATA and 6 NVMe interfaces
- Dual 1GbE or 10GbE ports with dedicated IPMI LAN port



H11 Generation WIO Serverboard

OPTIMIZED FOR STORAGE APPLICATIONS ON THE WIO PLATFORM



H11SSW


Single-socket WIO Form-Factor

- Up to 2nd Gen AMD EPYC processors, up to 225W TDP
- 16 DIMM slots, up to DDR4-3200MHz (1 DIMM per channel)
- 3 PCI-E 3.0 x16 and 2 M.2 slots
- Up to 16 SATA and 16 NVMe interfaces
- Dual 1GbE or 10GbE ports with dedicated IPMI LAN port



H11 Generation E-ATX Serverboard


DUAL-SOCKET PLATFORM FOR MAINSTREAM APPLICATIONS



H11DSi


Dual-socket E-ATX Form-Factor

- Up to 2nd Gen AMD EPYC processors, up to 225W TDP
- 16 DIMM slots, up to DDR4-3200MHz
- 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8 and 1 M.2 slots
- Up to 10 SATA and 2 NVMe interfaces
- Dual 1GbE or 10GbE ports with dedicated IPMI LAN port



H11 Generation ATX Serverboard

SINGLE-SOCKET PLATFORM FOR MAINSTREAM APPLICATIONS



H11SSL

Single-socket ATX Form-Factor

- Up to 2nd Gen AMD EPYC processors, up to 225W TDP
- 8 DIMM slots, up to DDR4-3200MHz
- 3 PCI-E 3.0 x16, 3 PCI-E 3.0 x8 and 1 M.2 slots
- Up to 16 SATA, 8 SAS and 2 NVMe interfaces
- Dual 1GbE or 10GbE ports



Storage Options

SAS3 ADD-ON CARD OPTIONS

CHOOSE YOUR ONBOARD I/O

Supermicro SIOM

Supermicro SAS3 add-on cards feature up to 16 internal SAS ports for high-performance storage applications. It addresses the growing demand for increased data throughput and scalability requirement across the enterprise-class server platforms and delivers cost effective storage solutions using SATA3 drives and maximum performance and reliability with SAS3 drives.

Mini-SAS cables may be required to purchase separately. For more product information and technical specifications, please visit supermicro.com or scan the QR code on the right to retrieve the complete list of options and verify your system compatibility.

12Gb/s

Serial Attached SCSI

SAS3 Host Bus Adapters in IT Mode			SAS3 RAID Adapters		
AOC-S3616L-L16iT	AOC-S3216L-L16iT	AOC-S3008L-L8e	AOC-S3108L-H8iR-16DD	AOC-S3108L-H8iR	AOC-S3008L-L8i
Broadcom® SAS 3616	Broadcom® SAS 3216	Broadcom® SAS 3008	Broadcom® SAS 3108	Broadcom® SAS 3108	Broadcom® SAS 3008
16 ports, 12Gb/s per port, 16 Internal, Low Profile, 1024 SATA/SAS Drives	16 ports, 12Gb/s per port, 16 Internal, Low Profile, 1024 SATA/SAS Drives	8 ports, 12Gb/s per port, 8 Internal, Low Profile, 122 SATA/SAS Drives	8 ports, 12Gb/s per port, 8 Internal, Low Profile, 16 SATA/SAS Drives	8 ports, 12Gb/s per port, 8 Internal, Low Profile, 240 SATA/SAS Drives	8 ports, 12Gb/s per port, 8 Internal, Low Profile, 63 SATA/SAS Drives

The Supermicro® Super I/O Module (SIOM) delivers up to 50% of I/O cost savings and freedom to select networking options from 1Gb/s to 100Gb/s through a Supermicro optimized form factor that is easy to scale, service and manage across a broad range of Supermicro server and storage systems. The SIOM also enables a higher degree of system integration and increased capacity by saving PCI-E slots that are traditionally reserved for add on cards.

For more product information and technical specifications, please visit supermicro.com

 AOC-MGP-i2M	 AOC-MGP-i4M	 AOC-MTGN-i2SM	 AOC-MTG-i4SM	 AOC-MTG-i2TM	 AOC-MTG-i4TM
 AOC-MTG-b2TM	 AOC-MH25G-b2S2GM	 AOC-MH25G-m2S2TM	 AOC-MHIBF-m2Q2GM	 AOC-MHIBF-m1Q2GM	 AOC-MHIBE-m1CGM



Fachsortiment

< >

Warenhaus-
Sortiment



Systeme in
genereller
Standard-
Ausführung

Standardsysteme nach Mass - ab Stange!

ABC SYSTEMS AG

APPLIED BRAINWARE & COMPUTER SYSTEMS

CH-8952 Schlieren
Rütistrasse 28
+41 43 433 6 433

CH-3007 Bern
Giessereiweg 9
+41 31 3 700 600

SAN@ABCsystems.ch
www.abcsystems.ch

Supermicro®, the leading innovator in high-performance, high-efficiency server technology is a premier provider of advanced server Building Block Solutions® for Data Center, Cloud Computing, Enterprise IT, Hadoop/Big Data, HPC and Embedded Systems worldwide. Supermicro is committed to protecting the environment through its "We Keep IT Green™" initiative and provides customers with the most energy-efficient, environmentally-friendly solutions available on the market.

Learn more at www.supermicro.com

Supermicro, the Supermicro logo, Building Block Solutions, We Keep IT Green, SuperServer, Twin, BigTwin, TwinPro, TwinPro², SuperDoctor are trademarks and/or registered trademarks of Super Micro Computer, Inc.

AMD, the AMD Arrow logo, EPYC™, and the EPYC™ logo are trademarks of Advanced Micro Devices, Inc. or its subsidiaries in the U.S. and/or other countries. All other brands names and trademarks are the property of their respective owners.

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

© Copyright Super Micro Computer, Inc. All rights reserved.